

# Coroplast<sup>®</sup> Synthetic HDPE Laminated Sheets



Coroplast<sup>®</sup> sheets are laminated with Tyvek<sup>®</sup> material and provide a cost-effective solution to our customers who need additional abrasion protection for their class “A” packaging application.

Based on the samples tested, the results indicate good adhesive integrity throughout the extreme temperature ranges (minus 10 degrees F).

As with all packaging applications, simulated transport testing should be conducted utilizing the actual packaging and parts to be protected as the configuration of the parts can play a significant role in the success or failure of protective packaging.

We believe the information contained in this bulletin is correct and to the best of our knowledge and tests. The recommendations and suggestions contained herein are made without guarantee or representation as to the results. We recommend that adequate tests be made in the customer’s laboratory or plant to determine if this product meets all of the customer’s requirements.

## Features & Benefits

- Lightweight and durable
- Made with 100% high density PE fibers
- Protects against moisture, oxygen, and other corrosives during transit and storage
- Weight: 1.6 ounces
- Thickness: 6.9 mils
- Tensile strength: 28 lbs (MD) & 28 lbs (CD)

Coroplast has gone through an extensive material qualification and testing program to ensure the proper combination of process, materials, and adhesion levels is well suited for our customer’s packaging needs.

Tyvek<sup>®</sup> is a registered trademark of DuPont or its affiliates. Copyright © 2019 DuPont de Nemours Inc.

## Coroplast<sup>®</sup>

TEL: 1-800-361-5150  
info@coroplast.com  
www.coroplast.com

OFFICE: 9 Peach Tree Hill Rd., Livingston, NJ 07039  
PLANT: Granby, QC; Vanceburg, KY